HIPPO CHEM

Special Cementitious Tile Adhesive

HK2

Special Cementitious Tile Adhesive is based on cement and copolymer resins. It is composed of cement and graded siliceous aggregates, and also contains powder polymers and other natural and mineral modifiers.

Features

- High bonding strength
- Long pot life
- High flexibility
- Moisture-resistant
- Resistant to temperature variations

Applications

- Installation of all types of ceramic and porcelain tiles up to 60 × 80 cm
- Installation of all kinds of stone and mosaic in dry and wet environments
- Tile-on-tile installation (the underlying tile surface must be roughened)

Method of use: The surface must be completely clean and free of any contamination, loose areas, grease, etc. First pour the required amount of water into a container, then mix using a suitable mechanical mixer until a uniform, lump-free product is obtained. After mixing and obtaining a homogeneous product, let it rest for 5 minutes, and then continue mixing. Apply the prepared paste to the surface using a notched trowel. Mix 20 kg of powder with 5 liters of water (mixing ratio 4 to 1).

Coverage: Typically, 3.5 kg of powder covers one square meter.

Property	Result	Test	Standard Limit (INSO 12492)	Company Test Results
Physical state	Powder	Initial tensile adhesion strength (N/mm^2)	Greater than 1	1.30
Color	White / Gray	Tensile adhesion strength after water immersion (N/mm^2)	Greater than 1	1.19
Density	1.6 g/cm^3	Tensile adhesion strength after heat aging (N/mm^2)	Greater than 1	1.05
Open time (at 20 to 30 °C)	30 minutes	Tensile adhesion strength after freeze–thaw cycles (N/mm^2)	Greater than 1	1.24
Ready for service after	24 hours	Tensile adhesion strength at open time (N/mm^2)	Greater than 1	1.09
Pot life	60 minutes			
Chloride ions	None			
Classification (INSO 12492)	C2			

Packaging	20 kg bag
Shelf life	One year in original packaging
Storage conditions	Protect from cold and frost, heat, and direct or prolonged sunlight
Recommended storage temperature	+10 to +30 °C

Address: Mostafa Khomeini Industrial Town, Phase 1, Sari, Mazandaran, Iran (corner of Golestan 3 West Alley)
WhatsApp: +98 915 789 2300

تولیدکننده افزودنی های بتن، ژل میکروسیلیس و چسب های ساختمانی | شیدور پارس SHIDVAR PARS